

DESCRIPTION:

Hand Cleaner. Natural citrus based biodegradable hand cleaner, leaves skin non slip and helps control industrial dermatitis promoting rapid healing of work wounds. Removes oils, grease, grime, tar, glues, including two pot glues and resins before curing.

CHARACTERISTICS:

No Harsh Solvents

Some cleaners use harsh solvents such as hydrocarbons (kerosene/paraffin), ammonia and chlorinated compounds which remove the skins natural oils leaving hands dry and easily chafed. Mainlube 590 is blended from oils of the pacific islands palms, by-products of cultivated citrus plants grown in tropical regions, sugar cane and animals products. This combination not only offers a truly natural organic product, but also assists in the reduction of environmental contamination, firstly by utilising by-products from food processes and secondly by reducing the amounts of synthetic and petrochemical contamination in the environment.

An outstanding cleaning action is provided by carefully selected natural solvents, which both break down and dislodge the most stubborn ingrained dirt.

Promotes Rapid Healing And Conditions Skin

590 Will assist with healing of environmental dermatitis, minor abrasions and wounds. 590 contains natural biodegradable anti-fungal, anti-septic and anti-bacterial properties. Mainlube 590 contains lanolin and other selected skin emollients which condition the skin and prevent dryness and cracking. Mainlube 415 Skin Guard will compliment 590 by protecting hands while working and preventing dirt and grease from penetrating into skin.

Mainlube 590 Is Effective In Removing:

Ingrained dirt and grease	Asphalt	Foundry dross	Dyes
Printers ink	Chalk	Carbon	Oil
Adhesives	Grime	Gum	Fats
		Solvents	Fine metal dust

Mainlube 590 Will Not Harm:

Nylon	Leather	Ceramics	Vitreous enamel and Any Metals
-------	---------	----------	--------------------------------

The tendency of soaps and other abrasive cleaners to clog drains is eliminated when using Mainlube 590.

HOW TO APPLY:

1. Rub a small amount of 590 into hands and knead each and with the other putting Mainlube 590 into full action.
2. While rubbing, slightly Wet hands to increase fluidity if desired.
3. Allow time for 590's Natural solvents to loosing dirt, we recommend the use of a soft nail brush to ensure all dirt is removed.
4. Rinse with water or wipe dirt away with a rag.
5. On a difficult cleaning operation such as Paint, Glue and Resins, leave Mainlube 590 on the hands for a few minutes to take advantage of Mainlube 590's full cleaning action.
6. Hands damage will be minimised with exposure to petrol and strong solvents if you use Mainlube 590 immediately after contact.

DISTRIBUTED BY:



ILS Engineering Ltd
Unit 15 Bullford Business Campus
Kilcoole
Co. Wicklow
Ireland
Tel: 00353 1 2875859 Fax: 00353 1 2875863 E-mail: info@ilsltd.com